



**Solinst®**

**LevelVent 5**

[More Info](#) | [Instructions](#) | [Get Quote](#)

**Model 3250 Data Sheet**



## LevelVent 5 Water Level Datalogger Model 3250

The Solinst LevelVent 5 is a vented version of our popular Levellogger®. The highly-accurate datalogger is designed to record water level and temperature measurements during shallow groundwater and surface water deployments.

The LevelVent 5 logger contains pressure and temperature sensors, a battery, memory for up to 150,000 data logs, and hydrophobic filter within a 22 mm x 173 mm (7/8" x 6.8") stainless steel housing with a corrosion-resistant coating.

The LevelVent uses a gauged pressure transducer; it is open to the atmosphere via a vented cable to the wellhead. The compact LevelVent wellhead is designed to fit in a Solinst 2" Well Cap Assembly, and provides easy connection for communication accessories.

The vented cable and Solinst LevelVent 5 logger are protected from moisture by permanent, built-in desiccants and hydrophobic filters in the logger and the wellhead.

The vented pressure transducer is made of Hastelloy®, making it extremely durable and accurate in a wide range of temperature and monitoring conditions. The sensor provides an accuracy of 0.05% FS, and can withstand 2 times over-pressure without permanent damage.

## LevelVent 5 Applications

- Ideal for shallow deployment: up to 20 m (65 ft) submergence
- Aquifer characterization: pumping tests, slug tests, etc.
- Stream gauging, lake, reservoir and dam management
- Watershed, drainage basin and recharge monitoring
- Stormwater and runoff monitoring
- Water supply and tank level measurement
- Long-term water level monitoring in wells and surface water

## Vented Datalogger Advantages

- Continuous, reliable water level data for long-term monitoring projects
- No barometric compensation required, saving data processing time
- Instant water level data for real-time aquifer test results



## LevelVent 5 Programming & Communication

The LevelVent 5 is programmed and data downloaded using Solinst Levellogger Software and a PC Interface Cable. It can also be used with the Solinst Levellogger 5 App Interface and DataGrabber 5. Both accessories and PC Interface Cable conveniently connect directly to the LevelVent 5 wellhead.

Integrate the LevelVent 5 with Solinst Telemetry Systems, which use the latest wireless technologies.

For deeper, hard to access applications, or areas that are prone to flooding, the Levellogger 5 Series of absolute pressure water level dataloggers are also options (see Model 3001 Levellogger 5 Series Data Sheet).

## LevelVent Features

- Corrosion and abrasion-resistant coating baked-on using polymerization technology
- Gauged pressure sensor for highly-accurate water level measurements: 0.05% FS
- Compact wellhead makes deployment simple using a Solinst 2" Well Cap Assembly
- Communication cables and accessories connect directly to the wellhead
- Long-lasting battery included in logger
- Built-in hydrophobic filters and desiccants – no need to replace, reduces maintenance

®Solinst and Levellogger are registered trademarks of Solinst Canada Ltd.  
®Hastelloy is a registered trademark of Haynes International Inc.

**High Quality Groundwater and Surface Water Monitoring Instrumentation**

**Solinst®**



# Solinst®

# LevelVent 5

## LevelVent 5 Logger Specifications

<b>Level Sensor:</b>	Piezoresistive Silicon with Hastelloy Sensor
Accuracy:	± 0.05% FS Typical
Stability of Readings:	Superior, low noise
Resolution:	0.001% FS to 0.0006% FS
Units of Measure:	m, cm, ft., psi, kPa, bar, °C, °F
Normalization:	Automatic Temperature Compensation
Temp. Comp. Range:	0° to 50°C
<b>Temperature Sensor:</b>	Platinum Resistance Temperature Detector (RTD)
Operating Temperature:	-20°C to 80°C
Temp. Sensor Accuracy:	± 0.05°C
Temp. Sensor Resolution:	0.003°C
Battery Life Estimate:	10 Years — based on 1 reading/minute
Clock Accuracy (typical):	± 1 minute/year (-20°C to 80°C)
Maximum # Readings:	150,000 sets of readings
Memory:	Slate and Continuous
Communication:	9600 bps Solinst USB
Size:	22 mm x 173 mm (7/8" x 6.8")
Weight:	190 grams (6.7 oz)
Corrosion Resistance:	Baked-on coating using polymerization technology (inside and out)
Wetted Materials:	Delrin®, Viton®, Polyurethane (TPU boot) 316L stainless steel, Hastelloy, PFAS-free PTFE coating
Sampling Modes:	Linear, User-Selectable with Repeat Mode, & Event, Future Start, Future Stop, Real-Time View
Measurement Rates:	1/8 sec to 99 hrs
Barometric Compensation:	Automatic

Models	Full Scale (FS)	Accuracy	Resolution
<b>M5</b>	5 m (16.4 ft)	± 0.3 cm (0.010 ft)	0.001% FS
<b>M10</b>	10 m (32.8 ft)	± 0.5 cm (0.016 ft)	0.0006% FS
<b>M20</b>	20 m (65.6 ft)	± 1 cm (0.032 ft)	0.0006% FS

## LevelVent 5 Wellhead

Materials:	Black Delrin, Nickel plated Zinc, Viton
Dimensions:	30 mm x 76 mm (1.2" x 3.0")
Operating Temperature:	-20°C to 80°C
IP Rating:	IP 64 (dust and splash proof)

\*The Apple logo is a trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Solinst Canada Ltd. is under license.  
\*Delrin and Viton are registered trademarks of DuPont Corp.

## LevelVent 5 Vented Cable Options

Solinst LevelVent 5 vented cable assemblies are available in custom lengths of up to 500 feet.

Vented cables contain communication wires, as well as a vent tube running the length of the cable. Vented cables provide direct read communication from the LevelVent 5 logger to the wellhead. The vent tube and wires are jacketed in polyurethane, providing durability and protection.

The vented cables are easily and securely connected to the LevelVent 5 logger and wellhead, using twist connections. A 2" Well Cap Assembly and hanger bracket are included to support the wellhead and vented cable when deployed.

## LevelVent 5 Vented Cable

Wetted Materials:	Polyurethane, Nickel plated Brass, Viton
Diameter:	Cable: 8 mm (0.32") Connectors: 20 mm (0.79")
Lengths:	1 to 500 ft
Max. Bend Radius:	25 mm (1")
Operating Temperature:	-20°C to 80°C


## Telemetry Applications



Integrate the LevelVent 5 with Solinst Telemetry Systems, which use the latest wireless technologies.

## Solinst Levellogger 5 App Interface

The Levellogger 5 App Interface uses *Bluetooth®* technology to connect your LevelVent 5 to your smart device. With the Solinst Levellogger App, you can download data, view real-time data, and program your dataloggers (see Model 3001 Levellogger 5 App Interface data sheets).



## DataGrabber 5

The DataGrabber 5 is a field-ready data transfer device that allows you to copy data from a LevelVent 5 onto a USB flash drive key, with one push-button. The DataGrabber 5 is compact and very easy to transport.

