


AC155 Series

Low Cost Triaxial Accelerometer, Top Exit 4 Pin Mini-MIL Connector, Follows Cartesian Phase Coordinate System, for Modal & ODS Analysis, 100 mV/g, ±15%



Product Features


Collect 3 Channels of Data Simultaneously for Faster Data Collection

Follows Cartesian Coordinate Phase Configuration (Right Hand Rule)

- ▶ Popularly used for Modal Analysis and ODS (Operating Deflection Shape)
- ▶ Compatible with CTC J Series Mini-MIL Connectors

AC155-1D 4 Pin Connector

Connector	Polarity
Pin	
A (Axis Y/3)	(+) Signal/Power
B (Axis X/2)	(+) Signal/Power
C (Axis Z/1)	(+) Signal/Power
D	(-) Common/Grid



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC155	M/AC155	Environmental		
Sensitivity (±15%)	100 mV/g		Operating Temperature Range	-65 to 250°F	-54 to 121°C
Frequency Response (±3dB)	36-390,000 CPM	0,6-6500 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 50 g, peak		Sealing	Welded, Hermetic	
	*Vsource ≥ 22V, 12Vbias		SIL Rating	SIL 2	
			Physical		
Electrical			Sensing Element	PZT Ceramic	
Settling Time	<2.5 seconds		Sensing Structure	Shear Mode	
Voltage Source (IEPE)	18-30 VDC		Weight	7.1 oz	200 grams
Constant Current Excitation	2-10 mA		Case Material	316L	
Spectral Noise @ 10 Hz	27 µg/√Hz			Stainless Steel	
Spectral Noise @ 100 Hz	6.5 µg/√Hz			1/4-28	
Spectral Noise @ 1000 Hz	2.5 µg/√Hz		Mounting Thread	Blind Tapped Hole	
Output Impedance	<100 ohm			4 Pin Mini	
Bias Output Voltage	10-14 VDC			MIL	
Case Isolation	> 10 ⁸ ohm				
			Connector (Non-Integral)		