



# VAISALA

Dew point and temperature probe DMP6  
 For dew point measurement in very high temperatures up to 350 °C

		DMPX	6	C	1	C	0				0		
			Probe head and cable	Probe cable	Sensor type	Filter type	Operating pressure	Baud rate	Parity, data bit, stop bit	Probe Modbus address	Reserved	Probe mounting accessory	Connection cable
1	Probe head and cable DMP6 for very high temperatures	6	6	C	1	C	0				0		
2	Probe cable 2m 10m		C	G									
3	Sensor type DrycapS			1									
4	Filter type Grid filter for DMP6				C								
5	Operating pressure Setting for ppm and other calculated variables 1 bar (absolute)					0							
6	Baud rate 1) 19200 use with Indigo transmitters 9600							A B					
7	Parity, data bit, stop bit 1) 8,N,2 use with Indigo transmitters 8,E,1 8,O,1								0 2 4				
8	Probe Modbus address 1) 240 use with Indigo transmitters 110 120 130 140									A B C D E			
9	Reserved None										0		
10	Probe mounting accessory None (installation in an existing cooling set) Cooling set for DMP6, required for new installations											0 B	
11	Connection cable None 1,5m, open ends 10m, open ends												0 1 2

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

**Selections in bold are included in the prices of the basic versions.**

*Selections in italic are available at an extra price.*

Example of order code with typical settings:

For use with INDIGO transmitters	DMPX	6	C	1	C	0	A	0	A	0	B	0
For use with Modbus RTU	DMPX	6	C	1	C	0	A	0	A	0	B	2

Valid from: January 2023