VAISALA

V		point and t	emperature probe nes up to 40 bar		Probe head and cable	Probe cable	Sensor type	Filter type	Operating pressure	Baud rate	Parity, data bit, stop bit	Probe Modbus address	Reserved	Probe mounting accessory	Connection cable
				DMPX	8	F	2						0		
1	Probe head				•										
2	Probe cable		pressurized pipelines		8	l									
_	l Tobe cable	2m cable				F									
3	Sensor type						ı								
	"	DrycapM					2								
4	Filter type							•							
			stainless steel filter					Α							
			steel filter for vacuum					В							
5	Operating p		Setting for ppm and other calculated variables												
	1)	1 bar (abs							0						
		3 bar (abs 5 bar (abs							1						
		7 bar (abs							3						
		9 bar (abs							4						
6	Baud rate	,	, , , , , ,							ı					
	1)	19200	use with Indigo transmitters							Α					
		9600								В					
7	Parity, data														
	1)	8,N,2	use with Indigo transmitters								0				
		8,E,1									2				
8	Probe Modk	8,O,1									4	l			
o	1)	240	use with Indigo transmitters									Α			
	''	110	aso with margo transmitters									В			
		120										С			
		130										D			
9	Reserved												•		
		None											0		
10	Probe mou														
			ing body with leak screw, R1/2" ISO											F	
			ing body without leak screw, R1/2" ISO											G	
			ing body without leak screw, NPT1/2"											H	
			ng body set for: R1/2" ISO with leak screw + NPT1/2" installation kit											J M	
11	Connection		III StallatiOII KIL											IVI	
**		None													0
		1,5m, ope	n ends												1
		10m, oper													2
	1	, -,													

¹⁰m, open ends 1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

For use with INDIGO transmitters	DMPX	8	F	2	Α	0	Α	0	Α	0	J	0
For use with Modbus RTU	DMPX	8	F	2	Α	0	Α	0	Α	0	J	2

Valid from: October 2022