

VAISALA

Order form
Orderer

Valid from April 2011
Order no.

DMT132 Dewpoint Transmitter

Vaisala HUMICAP® Dewpoint Transmitter		DMT132		A	A						PRICE
Parameter and scaling 4...20 mA	Dewpoint, scaling -20...+40 °C (-4...104 °F)	A									
	Dewpoint, free scaling °C	X									
	Dewpoint, free scaling °F	W									
	Tdf atm free scaling °C	Y									
	Tdf atm free scaling °F	Z									
Pressure setting for optimized accuracy and Tdf atm calculation	1 bar (abs)	1									
	3 bar	2									
	5 bar	3									
	7 bar	4									
	special (max 20 bar abs) Define value: _____	X									
Settings	Standard		A								
Sensor Protection	Standard tube filter		A								
Cable	no cable			0							
	0.3 m (1.0 ft) shielded output cable M8, threaded connector			1							
	3 m (9.8 ft) shielded output cable M8, threaded connector			2							
	5 m (16.4 ft) shielded output cable M8, threaded connector			3							
	10 m (32.8 ft) shielded output cable M8, threaded connector			4							
Limit LED (Port II)	no LED indication		A								
	LED with dewpoint setpoint +10 °C (+50 °F)		B								
	LED with special Td setpoint Define value: _____ °C		C								
Installation accessories	no accessories			0							
	NPT1/2" adapter			1							
	Basic sampling cell DMT242SC			2							
	Sampling cell with swagelok 1/4" male connectors DMT242SC2			3							
	Sampling cell with quick connector and leak screw DSC74			4							
	Two-pressure sampling cell DSC74B			5							
	Two-pressure sampling cell with coil DSC74C			6							
User' s guide language	No user' s guide		A								
	Multilingual guide		M								
Special features	None			0							
										TOTAL	
										QTY	
										TOTAL VALUE	

*Tdf atm is the dewpoint value calculated back to atmospheric pressure
Below 0 °C the transmitter outputs frostpoint

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:
DMT132 A 4 A A 2 A 0 M 0

End customer: _____

- Accessories:
- 226476
230602
230914
210662SP
219690
219980
230388
218773
222507
221525SP
HUMICAP180R

Loop-powered display 4...20 mA, Nokeval 301
Tube filter
Special cover set for HMK15 (fits DMT132 and HMP110)
NPT Adapter
USB Service cable
Connection cable to DM70/HM70
LED plug
ISO" 1/2 plug
NPT1/2" plug
Sealing ring set (3 pcs U-seal)
Humicap180R spare sensor