



Diode-Pumped Solid-State Laser Kit

LASKIT®-500

For Education & Research

Five different laser sources at the price of one!



Laser kit with various options

Five Modes of Operation

- CW @ 1064 nm
- Q-switched @ 1064 nm
- Intracavity Frequency Doubled CW @ 532 nm
- Intracavity Frequency Doubled and Q-Switched @ 532 nm
- External Frequency Doubling of the Q-Switched 1064 nm

Applications

- Education in Theory & Practice
- Laser & Optics Research & Testing
- Laser-Matter Interaction
- Start-Up for DPSS Laser Development

The LASKIT®-500 is a multipurpose laser source aimed at education, research and testing. In fact, it is the most versatile DPSS laser kit on the market, featuring *five* modes of operation.

The following fundamentals of laser theory and practice can be investigated*:

- Stability regions of laser cavity
- Various transversal cavity modes (TEM_{00} and higher)
- Optimum cavity configuration for TEM_{00} mode
- Optimum output coupling
- Laser threshold and differential efficiency
- Passive Q-switching threshold phenomena, pulse forms, optimization for maximum output power and maximum output energy, shortest pulse conditions
- Internal frequency doubling in CW-operation
- External frequency doubling in Q-switched mode
- Fluorescence lifetime of the active medium
- Laser dynamics (relaxation oscillations, Q-switching), dependence on active medium parameters; comparison between different active media (Nd:YAG and Nd:YVO₄)

*Suggestions only.

A fiber-pumped version is also available

The LASKIT®-500 includes:

- Pump laser diode with Peltier cooler and attached pump optics
- Laser diode driver & thermoelectric controller LDD1-1T (optional: LPS1-2T, microprocessor-controlled)
- Laser crystal Nd:YAG (Nd:YVO₄ optional), with a heat sink
- Set of two laser cavity mirrors (flat/curved)
- Cr⁴⁺:YAG passive Q-switch, AR/AR coated
- KTP frequency doubler with special coatings, in a holder
- Mirror and crystal mounts (3 pieces)
- Optical bench
- Diode laser module (670 nm) for aligning the laser cavity, with holder
- Infrared-to-visible converter (model IR-VIS-15-B), Ø 15 mm, for aligning the IR laser and mode analysis (also suitable for high-power lasers)
- Ultrafast photo detector (model UPD-300-SP) with rise time <300 ps, spectral range 320 - 1100 nm, external power supply, suitable for observing the relaxation oscillations and pulse duration of the Q-switched mode
- CCD linear array (model CCD-2000M) with 2048 pixels, high sensitivity, driver electronics and power supply, suitable for laser beam analysis, M² measurements, autocorrelators, etc.

The laser crystal, the passive Q-switch and the KTP-doubler are mounted in special holders for fast and easy exchange, alignment and handling. Switching from one mode of operation to another (e.g. from CW to Q-switched, or from IR to frequency doubling) can be done in a minute.

Special discounts for educational and research institutions!

DPSS Laser Kit

LASKIT®-500 • Modes of Operation

Mode of Operation	Output Power Nd:YAG Laser Crystal	Output Power Nd:YVO ₄ Laser Crystal	Pulse Duration / Repetition Rate	Comments
CW @ 1064 nm	min. 300 mW typ. 500 mW	min. 300 mW typ. 500 mW	Not applicable	TEM ₀₀ with plano-concave cavity.
Q-Switched @ 1064 nm	min. 80 mW typ. 100 mW	min. 80 mW typ. 100 mW	Nd:YAG : 10 - 50 ns, 5 - 50 kHz Nd:YVO ₄ : 50 - 100 ns, 50 - 100 kHz	Passively Q-switched with Cr ⁴⁺ :YAG crystal.
CW @ 532 nm	min. 10 mW typ. 15 mW	min. 20 mW typ. 40 mW	Not applicable	Intracavity frequency doubled.
Q-Switched @ 532 nm	min. 20 mW typ. 25 mW	min. 5 mW typ. 10 mW	Nd:YAG : 10 - 30 ns Nd:YVO ₄ : 50 - 100 ns	Intracavity frequency doubled & pas- sively Q-switched with Cr ⁴⁺ :YAG crystal.
Q-Switched @ 532 nm	min. 20 mW typ. 30 mW	min. 3 mW typ. 5 mW	Nd:YAG : 10 - 40 ns Nd:YVO ₄ : 50 - 100 ns	See -E-SHG option below. External fre- quency doubling, with optional 8 mm long KTP crystal & focusing lens.

LASKIT®-500 • Optional Upgrades*

* Multiple upgrades can be ordered with one laser kit.

Upgrade	Description	Average Power	Output Energy	Pulse Duration	Peak Power	Comments
-EOD	Actively Q-Switched @ 1064 nm (Nd ³⁺ :YAG)	typ. 20 mW @ 1 kHz typ. 100 mW @ 10 kHz	typ. 20 μJ @ 1 kHz typ. 10 μJ @ 10 kHz	typ. 25 ns @ 1 kHz typ. 50 ns @ 10 kHz	typ. 1 kW @ 1 kHz typ. 0.2 kW @ 10 kHz	Electro-Optic Deflector (EOD) as the active Q-switch. Operating voltage: max. 1 kV, HV pulse duration <1 μs.
-PC	Actively Q-Switched @ 1064 nm (Nd ³⁺ :YAG)	typ. 35 mW @ 1 kHz typ. 100 mW @ 10 kHz	typ. 35 μJ @ 1 kHz typ. 10 μJ @ 10 kHz	typ. 35 ns @ 1 kHz typ. 50 ns @ 10 kHz	typ. 1 kW @ 1 kHz typ. 0.2 kW @ 10 kHz	Pockels Cell as the active Q-switch. Operating voltage: max. 1 kV, HV pulse duration <1 μs.
-MC	Monolithic MICROCHIP Laser (Cr ⁴⁺ :Nd ³⁺ :YAG)	min. 120 mW typ. 140 mW	min. 5 μJ typ. 10 μJ	typ. 800 ps	typ. 10 kW	External frequency doubling, min. 40% efficiency with optional 8 mm KTP crystal and a lens.
-E-SHG	External Frequency Doubling @ 532 nm					
-THG	External Frequency Tripling @ 355 nm					
-FHG	External Frequency Quadrupling @ 266 nm					

- **Active Q-Switching:** Explore the superior alternative to the Pockels cell Q-switch: The EOD option implements an electro-optic deflector as the Q-switch. A high-speed driver is included. The low-voltage (<1 kV) short-pulse (<1 μs) design assures safe operation. Classical active Q-switching with a Pockels Cell is also available (PC option).
- **Monolithic Cr⁴⁺:Nd³⁺:YAG MICROCHIP Laser:** Generates high peak-power subnanosecond laser pulses at 1064 nm. The microchip laser needs no alignment because the laser mirrors are deposited directly on the laser crystal faces. The laser chip runs immediately when pumped with the laser diode of the laser kit. Best suited as a research tool in nonlinear optics, micromachining, laser-matter interaction, etc.

Related Product

- **Laser Power Meter (Model LPM-12):** This device complements the laser kit to build a complete laser laboratory measurement instrumentation. The power meter employs a broadband (0.2 - 10 μm) thermopile detector unit with an analogue output and a digital display.

Picosecond Laser Kit

A Picosecond Laser Kit (Model LASKIT®-pico) is also available. This diode-pumped passively mode-locked laser kit is sold at a fraction of the price of commercial lasers:

- Wavelength: 1064 nm
- Output Power: 300 mW
- Pulse Duration: 10 ps
- Repetition Rate: 100 MHz
- Semiconductor Saturable Absorber Technology

Please refer to the separate data sheet.

Laser Safety

This product is intended for expert users only. The laser kit is sold as a set of components; it is not a complete laser. The laser kit may only be assembled, installed and operated under the strict supervision and instructions of qualified personnel who are aware of ALL applicable laser safety rules and standards. These qualified personnel must be experts and must have excellent knowledge of laser design, laser construction as well as principles of laser operation. ALPHALAS GmbH assumes no liability whatsoever, expressed or implied, for the use of this product, nor its assembly or installation. Although the laser kit has been designed to comply with the international standard for safety of laser products IEC 60825-1 and the corresponding European standard EN 60825-1, it can ONLY comply with these standards if properly assembled by qualified personnel. The laser kit is for laser laboratory use ONLY (i.e. training, education or research). It is NOT for household or other uses. Students are NOT allowed to work with the laser kit without authorized supervision. The training, educational or research establishment of the customer shall take all necessary measures to ensure that ALL laser safety requirements are met.



VISIBLE AND INVISIBLE LASER RADIATION
AVOID EYE OR SKIN EXPOSURE TO
DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT

Max. Avg. Power: 5 W
Max. Peak Power: 50 kW
Pulse Duration: <1 ns - CW
Wavelengths: 1064, 808, 532, 355, 266 nm

ONLY IF PROPERLY
ASSEMBLED:
Compliant with
IEC 60825-1
2007-03

Always use suitable
laser safety protective
eyewear!

ALPHALAS GMBH
Bertha-von-Suttner-Str. 5
D-37085 Goettingen
Germany

TEL +49 - 551 - 77 06 147
FAX +49 - 551 - 77 06 146
E-MAIL sales@alphalas.com
WEB www.alphalas.com

LASERS, OPTICS, ELECTRONICS.
MADE IN GERMANY.
WWW.ALPHALAS.COM



Options and further specifications are available upon request. Specifications in this data sheet are subject to change without notice. No responsibility for typing or printing errors. ALPHALAS GmbH reserves the right to make changes without further notice to any products herein. ALPHALAS GmbH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ALPHALAS GmbH assume any liability arising out of the application or use of any product, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in ALPHALAS GmbH data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals", must be validated for each customer application by customer's technical experts. ALPHALAS GmbH products are intended for expert users only. ALPHALAS GmbH products are not designed, intended, or authorized for use in medical, surgical or any other human *in vivo* applications, or for any other application in which the failure of the ALPHALAS GmbH product could create a situation where personal injury or death may occur. Therefore, ALPHALAS GmbH products must not be used in such applications. Furthermore, ALPHALAS GmbH products must not be used in critical applications (e.g. in life support systems, in aviation, in nuclear facilities, in weapon systems, in safety or security systems, etc.). ALPHALAS GmbH products must not be used where damage to property may occur.