



VAISALA

Order form Orderer

Valid from December 2013

DPT145 Multiparameter transmitter for SF6 gas

	Vaisala Multiparameter T	Fransmitter DPT145 A A A	A	i I		Α	I	PRICE
1	Probe	DPT145 base - probe with UNF 7/8- 14 thread A						
2	Measurement parameters	Td/f, Td/f atm, ppm, P, Pnorm, density and T for SF6 gas 1						
		Td/f, Td/f atm, ppm, P, Pnorm, density and T for mixed SF6/N2 gas, %SF6%N2 2						
3	Digital output	RS-485 A						
		RS-485 with Modbus RTU mode by default M						
l,5	Reserved codes	A	Δ.					
5	Output units	Metric units (Celsius, bara)	1					
		Non-metric units (Fahrenheit, psia)	2					
,	Mechanical connection	DILO DN8 connector		1				
ĺ		DILO DN20 connector		В				
		ABB connector		С				
		Alstom connector		D				
	Cable for RS485 output	None			0			
	and power supply	1,5 m Shielded PUR cable with 90° connector			1			
		3 m Shielded PUR cable with 90° connector		:	2			
		5 m Shielded PUR cable with 90° connector		1	3			
		10 m Shielded PUR cable with 90° connector			4			
		3 m Shielded FEP cable with straight connector (Compatible w. combination of Alstom connector + Rain shield)		1	5			
		15 m Shielded PUR cable with straight connector		1	6			
		20 m Shielded PUR cable with straight connector			7			
	Installation accessories	None			0			
		Weather shield			1			
0	Special features	None				A	Γ	
1	User' s guide	None					Α	
		Multilingual quick guide					х	
						т	otal	

Selections in bold are included in the prices of the basic versions. Selections in italic are available at an extra price.

DPT145 A I A A I B I I A X

End customer:

Accessories and spare parts								
219980	Connection cable for DM70							
219690	USB Serial Interface Cable							
218675SP	Protection plug for connector							
231519SP	1.5 m Shielded PUR cable with 90° connector							
231520SP	3 m Shielded PUR cable with 90° connector							
231521SP	5 m Shielded PUR cable with 90° connector							
231522SP	10 m Shielded PUR cable with 90° connector							
226902SP	3 m Shielded FEP cable with straight connector							
236407SP	15 m Shielded PUR cable with straight connector							
235859SP ASM210326SP	20 m Shielded PUR cable with straight connector Weather shield							