

VAISALA

Order form
Orderer

Valid from 7 March 2013
Order no.

Vaisala CARBOCAP® Carbon Dioxide Probe GMP343

Fill here												PRICE
Vaisala CARBOCAP® Carbon Dioxide Probe		GMP343									0	
Sampling method	diffusion	A										
	flow through	B										
Measurement range of the probe:	0...1000 ppm CO ₂	1										
	0...2000 ppm CO ₂	2										
	0...3000 ppm CO ₂	3										
	0...4000 ppm CO ₂	4										
	0...5000 ppm CO ₂	5										
	0...2 % CO ₂ *	6										
Analog output selection **	0...5 V	A										
	0...2.5 V	B										
	4...20 mA	C										
Digital output selection	RS232	1										
	RS485 ***	2										
Probe cable	none											
	probe cable (with M12 type female connector), 2 m											
	probe cable (with M12 type female connector), 6 m											
	probe cable (with M12 type female connector), 10 m											
Measurement indicator MI70 and accessories	none											
	MI70 indicator and interface cable, 2 m ****											
	MI70 interface cable, 2 m											
Calibration accessories	none											
	calibration adapter for diffusion model											
	PC connection kit*****											
	calibration adapter for diffusion model and PC connection kit*****											
Mounting accessories	none											
	mounting flange											
Wiring accessories	none											
	junction box											
Special features	none											
User's Guide	no User's Guide											
	English											
	Japanese											
TOTAL												
QTY												
TOTAL VALUE												

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Example of order code:

GMP343	A	1	A	1	A	0	A	0	A	0	B
--------	---	---	---	---	---	---	---	---	---	---	---

End customer: _____

Notes for the selections:
* Accuracy below 200 ppmCO₂ not specified for the 2% range option
** The analog output type (current or voltage mode) may be selected and re-scaled using PC connection cable by customer
*** If the selection is RS485, the device may be powered up in the RS232 service mode for user settings. See User's Guide for details.
**** The selection includes:
- MI70 indicator with a rechargeable battery
- AC adapter with AUS, EUR, UK, and US plugs
- MI70Link software with RS232 cable (PC <-> MI70)
- 2 m interface cable (GMP343 <-> MI70)
***** The selection includes PC connection cable (213379) and USB adapter (USB-D9 Serial connection cable, 219686)

Note: following accessories are also available as a spare parts:			
ACCESSORY	CODE:	NOTE:	
Wall mount bracket	GMP343BRACKET	Included in the default configuration	
Mounting flange	GMP343FLANGE		
Standard diffusion filter (IP65) + filter cover	GMP343FILTER	Included in the default configuration of diffusion model	
Diffusion filter (sintered filter, IP66) + filter cover	215521		
Calibration adapter	GMP343ADAPTER		
Junction box	JUNCTIONBOX-8		
Probe cable (with M12 type female conn.), 2 m	GMP343Z200SP		
Probe cable (with M12 type female conn.), 6 m	GMP343Z600SP		
Probe cable (with M12 type female conn.), 10 m	GMP343Z1000SP		
PC connection cable	213379		
Interface cable for MI70, 2 m	DRW216050SP		
USB adapter (USB-D9 Serial connection cable)	219686		
Soil adapter kit for horizontal positioning	215519	Includes sintered PTFE filter	
Soil adapter kit for vertical positioning	215520	Includes sintered PTFE filter	