




# Owl 640 T

High Sensitivity, Digital VIS-SWIR camera  
640 x 512 • 10µm x 10µm Pixel Pitch • <50e readout noise •



## Key Features and Benefits

*The World’s first SWaP optimised ½” / VGA sensor with VIS-SWIR response*

- **½” Sensor Format**  
Better for optical design, ideal for OEM integration into Electro-Optic systems.
- **10µm x 10µm Pixel Pitch**  
Compatible with VIS-SWIR illuminators, markers & pointers
- **<50 Electrons Readout Noise**  
Enables highest VIS-SWIR detection limit
- **On-board Automated Gain Control (AGC)**  
Enables clear video in all light conditions
- **On-board Intelligent 3 point NUC**  
Enables highest quality photos

Resolution	640 x 512
Frame rate	10 to 60Hz
Camera link	12 bit
Wavelength Range	VIS-SWIR

Specification for Owl 640 T

Sensor Type	InGaAs PIN-Photodiode
Active Pixel	640 x 512
Pixel Pitch	10µm x 10µm
Active Area	6.4mm x 5.12mm
Spectral response <sup>1</sup>	0.6µm to 1.7µm
Readout Noise (RMS) <sup>2</sup> LG = Low Gain HG = High Gain	LG: <180e- (160e- typical) HG: <50e- (28e- typical)
Peak Quantum Efficiency	>90% @1.3µm
Full Well Capacity	LG: 450ke- HG: 10ke-
Pixel Operability	>99.5%
Dark Current (e/p/s)	<19,000 @ 15°C
Digital Output Format	12 bit Camera Link (Base Configuration)
Exposure time	LG: 20µs to 92.5ms HG: 40µs to 86.5ms
Shutter mode	Global shutter
Frame Rate	10 to 60Hz
Optical Interface <sup>3</sup>	C mount
Dynamic Range (Typical)	LG: 69dB, HG: 47dB
Trigger interface	Trigger IN and OUT - TTL compatible
Power supply	12V DC ±0.5V
TE Cooling	Active
Image Correction	3 point NUC (offset, Gain & Dark Current) + pixel correction
Functions controlled by serial communication	Exposure, intelligent AGC, Non Uniformity Correction, Gamma, Pk/Av, TEC, ALC ROI
Camera Power Consumption <sup>4</sup>	<8W with TEC ON, NUC ON
Operating Case Temperature <sup>5</sup>	-20°C to +55°C
Storage Temperature	-30°C to +60°C
Dimensions (L*W*H) <sup>6</sup>	67.60mm x 50.00mm x 50.00mm
Weight	247g

Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.

Ordering Information


<b>Camera</b>	
Owl 640 T Digital Camera	OW1.7-VS-CL-640-T
Power Supply Cable	RPL-HR4-K
<b>Optional Accessories</b>	
Mini PC with XCAP STD and frame grabber	RPL-PC-mf2280
Thunderbolt frame grabber	RPL-mf2280
EPIX® EB1 Frame Grabber	RPL-EPIX-EB1
EPIX® XCAP Std software	RPL-XCAP-STD
MDR-SDR CameraLink Cable (2m) <sup>7</sup>	RPL-MCL-CBL-2M
Optical Lenses <sup>8</sup>	RPL-xx-xxxx

- Note 1: Optional filters available: Low, High or bandpass.  
Note 2: Typical readout noise is calculated from an average of the last 20 cameras shipped.  
Note 3: Other mounts on request.  
Note 4: Measured in an ambient of 25°C with adequate heat sinking. For more detailed power consumption values, please refer to the user manual.  
Note 5: Extended operating temperature range on request.  
Note 6: Dimensions include all connector parts on the camera interface.  
Note 7: One cable required. The maximum cable length is 2m. For more information, please refer to the user manual.  
Note 8: Please consult us to check our range of lenses.  
Note 9: Windowless option available, please contact us for further details

Demo is available on request.  
Pricing AOR subject to volumes.

Detailed technical drawings  
can be downloaded at  
[www.raptorphotonics.com](http://www.raptorphotonics.com)

Quantum Efficiency



\*Data supplied by sensor manufacturer

Applications

- Surveillance**
  - 860, 1064 & 1550nm laser line detection
  - Airborne and Ground Payload
  - Hand Held Systems
  - Driving Vision Enhancement (DVE)
  - Airborne EVS
  - Vision enhancement
- Scientific**
  - Astronomy
  - Beam Profiling
  - Hyperspectral Imaging
  - Semiconductor Inspection
  - Solar Cell Inspection
  - Thermography