



VAISALA

TMW110
Wall mount Temperature Transmitter



TMW110 Order Form
G010039EN-A
Valid from August 2023

		1 2 3 4 5 6 7 8							
Wall mount Temperature Transmitter		TMW110			N	V	O		N
settings	1 Output Signals	4...20 mA 2-wire loop-powered	2						
	and display	• 4...20 mA 2-wire loop-powered, with display	4						
		Modbus RTU	N						
		• Modbus RTU, with display	N						
	2 Measured Parameter for Channel 1	T 0 ... +50°C (32 ... 122 °F)	1						
	and display ¹	T -5 ... +55°C (23 ... 131 °F)	2						
		T -40 ... +60°C (-40 ... 140 °F)	3						
		T special scale °C, please specify:	X						
		T special scale °F, please specify:	Y						
		No selection (Modbus model) ²	N	N	V	O			
acc.	6 User guide	No User's Guide						0	
		• Multilingual Quick Guide for HMDW110 Series						1	
hardware	7 Display options	Metric Units							1
		Non-Metric Units							2
		Metric units only (cannot be changed after delivery)							3
		No display							N

1) Selects output parameter for analog output and the display (in devices with display)
2) Choose No selection (Modbus model) for Modbus devices without display

NOTE: Selections in bold are included in the prices of the basic versions.
• Selections in italic are available at an extra price.
+ Suggested/default selection

LINKS: [User Guides](#)
[Datasheet](#)
[Vaisala.com product page](#)

Accessories and spare parts

- Conduit Fitting + O-Rin M16x1.5 / PG9, RE-MS
- Conduit Fitting + O-Rin M16x1.5 / NPT1/2 Inch
- USB Service Cable M8-4F, RS485
- MI70 Connection Cable with M8-4F Connector
- Terminal Block, Blue PK1304D 4P
- Membrane Filter PC White UV stabilized
- Porous PTFE Filter Ø12, L22mm

- 210674SP
- 210675SP
- 219690
- 219980SP
- 236620SP
- ASM210856SP
- DRW239993SP

Example of order code with typical settings:

		1 2 3 4 5 6 7 8							
Loop powered:	TMW110	2	3	N	V	O	O	N	N
Loop powered, display:	TMW110	4	3	N	V	O	O	1	N
Modbus,no display:	TMW110	M	N	N	V	O	O	N	N
Modbus,display:	TMW110	N	3	N	V	O	O	1	N