

TRCA330 Series

Miniature Industrial Triaxial Accelerometer, Side Exit 4 Pin Mini-MIL Connector, Follows Cartesian Phase Coordinate System, 10 mV/g, ±5%




Product Features

- Collect 3 Channels of Data Simultaneously for Faster Data Collection
- Follows Cartesian Coordinate Phase Configuration (Right Hand Rule)
 - ▶ High Performance Triaxial Sensor with High End Frequency Response of 15 kHz (+3dB)
 - ▶ Low Profile, Side Exit Case is Ideally Suited for Route Based Measurements
 - ▶ Compatible with CTC J Series Mini-MIL Connectors

TRCA330

4 Pin Mini-MIL Connector

Connector Pin	Polarity
A (Axis Y)	(+) Signal/Power
B (Axis X)	(+) Signal/Power
C (Axis Z)	(+) Signal/Power
D	(-) Common/Grid




Stock Product

TRCA430

CB105 Cable

Conductor	Polarity
Red (Axis Y)	(+) Signal/Power
Green (Axis X)	(+) Signal/Power
White (Axis Z)	(+) Signal/Power
Black	(-) Common/Grid




Built To Order

TRCA530

CB218 Armored Integral Cable

Conductor	Polarity
Red (Axis Y)	(+) Signal/Power
Green (Axis X)	(+) Signal/Power
White (Axis Z)	(+) Signal/Power
Black	(-) Common/Grid



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TRCA330	M/TRCA330	<u>Environmental</u>		
Sensitivity (±5%)	10 mV/g		Operating Temperature Range	-65 to 250°F	-54 to 121°C
Frequency Response (±3dB)	30-900,000 CPM	0.5 Hz-15 kHz	Maximum Shock Protection	10,000 g, peak	
Frequency Response (±10%)	60-480,000 CPM	1 Hz-8 kHz	Electromagnetic Sensitivity	CE	
Frequency Response (±5%)	480-330,000 CPM	8 Hz-5.5 kHz	Sealing	Welded, Hermetic	
Dynamic Range	±500 g, peak *Vsource ≥ 22V, 12Vbias		Submersible Depth	200 ft.	60 m
<u>Electrical</u>			SIL Rating	SIL 2	
Settling Time	<2.5 Seconds		<u>Physical</u>		
Voltage Source (IEPE)	18-30 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-10 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	100 µg/√Hz		Weight	3.9 oz	110 grams
Spectral Noise @ 100 Hz	19 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	5 µg/√Hz		Connector (Non-Integral)	4 Pin Mini-MIL	
Output Impedance	<100 ohm		Resonant Frequency	2,640,000 CPM	44 kHz
Bias Output Voltage	10-14 VDC		Mounting Torque	1 to 2 ft. lbs.	1,4 to 2,7 Nm
Case Isolation	>10 ⁸ ohm		Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate	CA10	

Typical Frequency Response

