



## UG11-UV

UV transmitting filter for BEAMAGE camera.



### PRODUCT FAMILY KEY FEATURES

#### UV BANDPASS FILTER

Particularly useful for applications with wavelengths contained between 250 nm and 370 nm. Other wavelengths are blocked by the filter.



## SPECIFICATIONS

### MEASUREMENT CAPABILITIES

Spectral range	250 - 370 nm
Parallelism	< 3 arcmin
Maximum power	1 W
Surface quality	40-20 Scratch-Dig
Surface flatness	< $\lambda/4$
Thickness	3 mm

### DAMAGE THRESHOLDS

Damage thresholds	30 W/cm2
-------------------	----------

### PHYSICAL CHARACTERISTICS

Dimensions	30.5Ø X 11.4D mm
Weight	0.04 kg
Mounting thread	SM1
Clear aperture	80% of area
Adaptor included	SM1 / C-Mount
Dimensional tolerance	+0.0/-0.2 mm

### ORDERING INFORMATION

UG11-UV	202602
---------	--------

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

## INTERESTED IN THIS PRODUCT?

GET A QUOTE



---

Find your local sales representative at [gentec-eo.com/contact-us](http://gentec-eo.com/contact-us)