



UP19K-200W-H9-D0

Thermal detector for laser power measurement up to 200 W.



PRODUCT FAMILY KEY FEATURES

- MODULAR CONCEPT**
Increase the power capability of your detector: 5 different cooling modules
- HIGH PERFORMANCE**
 - Fast rise time (0.6 sec)
 - High damage threshold (45 kW/cm²)
- COMPACT DESIGN**
Only 20.6 mm thick (15S model)
- ENERGY MODE**
Measure single shot energy up to 15 J
- SMART INTERFACE**
Containing all the calibration data
- COMPATIBLE STAND**
[STAND-S-233](#)



SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power (continuous) ¹	200 W
Maximum average power (1 minute) ²	200 W
Noise equivalent power ³	3 mW
Spectral range ⁴	0.193 - 20 μm
Typical rise time ⁵	1.5 s
Power calibration uncertainty ⁶	±2.5 %
Repeatability	±0.5 %

1. Minimum cooling flow 0.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

2. Minimum cooling flow 0.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

3. Nominal value, actual value depends on electrical noise in the measurement system.

4. For the calibrated spectral range, see the user manual.

5. With anticipation.

6. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

Maximum measurable energy ¹	25 J
Noise equivalent energy ²	0.06 J
Minimum repetition period	4 s
Maximum pulse width	88 ms
Energy calibration uncertainty ³	±5 %

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).

2. Nominal value, actual value depends on electrical noise in the measurement system.

3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

Maximum average power density ¹	45 kW/cm ²
Maximum energy density ²	1 J/cm ²

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.

2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.



PHYSICAL CHARACTERISTICS

Cooling	Water
Aperture diameter	19 mm
Absorber	H9
Dimensions	76.5H x 50W x 33D mm
Weight	0.24 kg

ORDERING INFORMATION

UP19K-200W-H9-D0	200582
UP19K-200W-H9-INT-D0	203045
UP19K-200W-H9-BLU-D0	203655
UP19K-200W-H9-IDR-D0	203343

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us