




PRODUCT



CS506-L

Fuel Moisture Sensor



Remote Measurements

Monitors forest-fire factor; ideal for use with RAWS

Overview

The CS506 is a fuel moisture sensor that measures the moisture content of the 26601 10-hour fuel moisture stick. The 26601 emulates the moisture content of similarly sized twigs on the forest floor. The CS506/26601 combination is used to assess

forest fire fuel and is often incorporated in our prewired or custom fire-weather stations.

Note: The image shows a CS506 fuel moisture sensor attached to a 26601 fuel moisture stick. The 26601 is purchased separately.

Benefits and Features

- › Compatible with most Campbell Scientific data loggers
- › Companion product to CS205/107 fuel temperature sensor; can be mounted on the same stake
- › Can automatically monitor changing fuel conditions without having to visit the measurement site
- › Compatible telemetry options include spread spectrum radios, narrow-band radios, cellular phones, and satellite transmitters

Detailed Description

The CS506 reports the status of small-diameter (10-hour) forest fire fuels as percent moisture by weight (1%=1 g water/100 g dry fuel). It consists of an epoxy-encapsulated electronics package that uses time-domain reflectometry (TDR) technology to measure the moisture content of the 26601 10-

hour Fuel Moisture Stick. The sensor produces a ± 0.7 Vdc square-wave frequency that is read using an analog or pulse channel on a Campbell Scientific data logger. The data logger then converts the frequency measurement to percent fuel moisture via a quadratic calibration.

Specifications

Operating Range 0 to 70% moisture content

Power Supply 5 to 18 Vdc





Enable Voltage	<div>› on at 5 Vdc (> 4 Vdc; maximum 18 Vdc)</div> <div>› off at 0 Vdc (< 1 Vdc)</div>
Current Consumption	<div>› 65 mA (active)</div> <div>› 45 µA (quiescent)</div>
Output Signal	±0.7 Vdc square wave (with an output frequency of approximately 31 to 58 kHz)
Dimensions	10.16 x 6.35 x 1.91 cm (4 x 2.5 x 0.75 in.)

Weight

< 0.5 kg (< 1 lb)

Fuel Moisture Accuracy

0 to 10% Range	<div>› ±1.25% (worst case)</div> <div>› ±0.74% (RMS error)</div>
10 to 20% Range	<div>› ±0.9% (RMS error)</div> <div>› ±2% (worst case)</div>
20 to 30% Range	<div>› ±3.4% (worst case)</div> <div>› ±1.94% (RMS error)</div>
30 to 50% Range	<div>› ±2.27% (RMS error)</div> <div>› ±4.11% (worst case)</div>

For comprehensive details, visit: www.campbellsci.com/cs506-l